

ADHESION PROMOTERS WITH EPOXY-REACTIVE GROUPS

Field of The Invention

The field of the invention is adhesion promoters.

5 Background of The Invention

In many composite materials, and particularly in composite materials that include rubber and polymeric fibers, adhesion between the polymeric fibers and the rubber is a significant factor in the overall performance of such composite materials, and numerous approaches are known in the art to improve adhesion between a polymeric fiber and a rubber composition.

10 In one approach, the surface of a polymeric fiber is physically modified with an electron beam to create particular chemically reactive groups that are then involved in forming covalent bonds between the polymeric fiber and the rubber as described in U.S. Pat. No. 4,794,041 to *Gillberg-LaForce et al.* Treating polyethylene terephthalate (PET) materials with an e-beam advantageously generates reactive groups (e.g., carboxylate or hydroxyl groups) on the PET surface, which may react with epoxy or isocyanate groups in the adhesive coating on the polymeric fiber to improve bonding between the PET material and a rubber. However, e-beam treatment tends to increase production cost. Moreover, *Gillberg-LaForce's* approach typically requires installation of relatively large and energy consuming equipment.

15 In another approach, the surface is chemically modified with a solvent to improve adhesion of a rubber composition of the fiber as described, for example, in U.S. Pat. No. 3,644,136 to *McCullough et al* or U.S. Pat. No. 3,902,950 to *Tung et al.* Surface treatment of a polymeric fiber is relatively simple, and may even be performed in some cases without specialized equipment. However, the use of halo-organic solvents in such treatments frequently poses environmental and/or health concerns. Moreover, surface treatment with halo-organic solvents typically still necessitates
20 in many cases the use of resorcinol-formaldehyde-latex (RFL) to improve rubber adhesion.

To circumvent at least some of the problems associated with surface treatments, polymeric fibers may be covered with an additional layer. Such layers may be applied in the form of a spin

finish, overfinish, or by dipping the polymeric fiber into one or more adhesives. There are numerous examples known in the art, and exemplary methods and compositions for spin-finish coating are described in U.S. Pat. No. 4,467,064 to *Kudo et al.* or U.S. Pat. No. 4,477,497 to *Kudo et al.*

Exemplary methods and compositions for over-finish coating are described in JP 8,246,353 to

5 *Kitahara et al.*, and exemplary methods and compositions for dip coating are described in U.S. Pat. No. 3,429,354 to *Malcom* or U.S. Pat. No. 3,903,332 to *Kelly et al.* Although providing additional layers onto the surface of polymeric fibers frequently improves the adhesion of rubber to the fibers, the additional layers generally still need an RFL adhesive coating, which is environmentally problematic and may pose significant health threats to workers exposed to resorcinol and formaldehyde.

10 In still other approaches, RFL is replaced with an acrylic resin with a molecular weight of between about 100,000 and 1,000,000 that is mixed with resorcinol-formaldehyde free latex as described by *Solomon et al.* in U.S. Pat. No. 4,472,463. While the use of *Solomon's* resins allows omission of RFL and tends to improve adhesion of latex to a substrate, the use of such resins typically requires a two-step dip process (e.g., a polyepoxide dip and an acrylic-rubber latex mixture). Moreover, *Solomon's* resins lack crosslinking functionalities to the latex, thereby potentially reducing optimal adhesion.

15 Alternatively, maleinized polybutadiene may be employed to eliminate the use of RFL as described in a paper presented at the 155th Rubber Division of the ACS, Chicago, Ill, April 13-16, 1999 ("Maleinized Polybutadiene Latex for Fiber to Rubber" by A. S. Estrin and R. W. Nalepa).

20 Although such compositions may advantageously replace RFL in some instances, maleinized polybutadiene has relatively poor water solubility and generally requires the use of sodium, potassium or ammonium hydroxides for formation of lattices and solutions in water. Moreover, adhesion of such compositions to fibers is at least in some cases less than desirable.

25 Although various methods and compositions for improving adhesion between a polymeric fiber and rubber are known in the art, all or almost all of them suffer from one or more disadvantages. Thus, there is still a need to provide compositions and methods for improved adhesion promoters.

Summary of the Invention

The present invention is directed to an adhesion promoter comprising a polymeric strand with an epoxy-reactive group other than a phenolic hydroxyl group and a crosslinking group, wherein the crosslinking group is capable of crosslinking the polymeric strand with a rubber in a crosslinking reaction, and wherein the polymeric strand is water soluble in an amount of no less than 10g/l, and more preferably no less than 100g/l.

In one aspect of the inventive subject matter, the polymeric strand comprises an organic polymer, preferably polybutadiene, and more preferably a polybutadiene that is maleinized and wherein at least one carboxyl group of the maleic acid is esterified with methoxy polyethylene glycol. Especially contemplated epoxy-reactive groups include carboxylic acid groups, and especially contemplated crosslinking groups comprise a double bond which may or may not be located within the backbone of the polymeric strand. Consequently, the crosslinking reaction may involve a covalent bond with a sulfur atom, or a nucleophilic/electrophilic addition, or a cyclo-addition.

In another aspect of the inventive subject matter, contemplated adhesion promoters further comprise a second polymer, preferably a styrene-butadiene-vinylpyridine copolymer (e.g., styrene-butadiene-vinylpyridine latex). Contemplated rubbers include synthetic and natural rubbers, and it is especially preferred that the rubber may further comprise polybutadiene grafted with maleic anhydride, or that the rubber may further comprise hexamethylene tetramine, resorcinol and silica.

In a further aspect of the inventive subject matter, a rubber containing product comprises a polymeric fiber coated with a compound having a plurality of epoxy groups, wherein the polymeric fiber is coupled to a rubber via an adhesion promoter. Contemplated adhesion promoters preferably comprise a polymeric strand with an epoxy-reactive group other than a phenolic hydroxyl group, and further comprise a crosslinking group that crosslinks the polymeric strand with the rubber, and have a water solubility of no less than 10g/l, and more preferably no less than 100g/l. Contemplated adhesion promoters may further comprise a second polymer, preferably a styrene-butadiene-vinylpyridine copolymer (e.g., styrene-butadiene-vinylpyridine latex).

10 In a still further aspect of the inventive subject matter, a method of fabricating a rubber-
containing product comprises a step in which rubber, and a polymeric fiber comprising a plurality of
epoxy groups are provided. In a further step, an adhesion promoter is provided having a polymeric
strand with an epoxy-reactive group other than a phenolic hydroxyl group, and further having a
5 crosslinking group, and wherein the adhesion promoter is water soluble in an amount of no less than
10g/l, and more preferably no less than 100g/l, and in a still further step the rubber is covalently
coupled with the polymeric fiber via the adhesion promoter, wherein the epoxy-reactive group forms
a covalent bond with the epoxy group, and wherein the crosslinking group forms another covalent
bond with the rubber. Contemplated adhesion promoters may further comprise a second polymer,
preferably a styrene-butadiene-vinylpyridine copolymer (e.g., styrene-butadiene-vinylpyridine latex).

Various objects, features, aspects and advantages of the present invention will become more
apparent from the following detailed description of preferred embodiments of the invention, along
with the accompanying drawing.

Brief Description of The Drawing

Figure 1 is a schematic of an exemplary adhesion promoter.

Figure 2 is a structure of an exemplary adhesion promoter.

Figure 3 is a structure of an exemplary second polymer.

Figure 4 is an exemplary synthetic scheme for an adhesion promoter.

Figures 5A and 5B are schematics of a portion of a tire comprising the adhesion promoter.

20 Figures 6A and 6B are schematics depicting an exemplary rubber containing product.

Figure 7 is a schematic depicting various contemplated interactions of an exemplary
adhesion promoter.

Detailed Description

The inventors have discovered that, among other desirable properties, contemplated adhesion promoters may replace RFL (resorcinol-formaldehyde-latex) as adhesion promoters in various rubber/fiber composite materials. In particular, contemplated adhesion promoters include an acid modified polybutadiene in which at least one acid group of a maleinized polybutadiene is modified with a group that increases the water solubility of the maleinized polybutadiene, and/or that increases chemical compatibility of the adhesion promoter to a polymeric fiber or other polymeric material.

Moreover, the inventors have discovered that a combination of contemplated adhesion promoters with a second polymer (preferably a styrene-butadiene-vinylpyridine latex) significantly increases the adhesion of a rubber to a polymeric fiber or yarn previously treated with contemplated adhesion promoters. Still further, the inventors have discovered that adhesion can be increased even more when the rubber comprises a maleinized polybutadiene or hexamethylenetetramine /resorcinol/silica.

Figure 1 depicts an exemplary adhesion promoter 100 having a polymeric strand 105 that includes a plurality of crosslinking (here: unsaturated) groups 120, all of which are located in the backbone of the polymeric strand. A plurality of epoxy-reactive groups 110 are coupled to the polymeric strand 105, wherein the epoxy reactive groups are groups other than a phenolic hydroxyl group.

In a particularly preferred aspect of the inventive subject matter, the polymeric strand 105 is a polybutadiene, wherein the crosslinking groups 120 comprise double bonds and wherein at least some of the crosslinking groups are located within the backbone of the polybutadiene. It should be recognized, however, that such crosslinking groups may also be located in a pendent position (e.g., in a 1,2-vinyl microstructure in polybutadiene). The epoxy-reactive groups 110 are pendent carboxylic acid groups of maleic acid moieties, which are covalently attached to the polymeric strand, and at least some of the carboxylic acid groups are modified (here: esterified) with methoxy polyethylene glycol (having between about 1-100 repeating alkoxy groups). However, it should be recognized that the use of unmodified maleinized polybutadiene *per se* or maleinized polybutadiene

lattices or solutions prepared by dissolving the maleinized polybutadiene in aqueous solutions containing sodium hydroxide, potassium hydroxide or ammonium hydroxide as adhesion promoter (as described in the paper presented at the 155th Rubber Division of the ACS, Chicago, Ill, April 13-16, 1999; "Maleinized Polybutadiene Latex for Fiber to Rubber" by A. S. Estrin and R. W. Nalepa) is particularly excluded. As used herein, the term "backbone" refers to a contiguous chain of atoms or moieties forming a strand that are covalently bound such that removal of any of the atoms or moiety would result in interruption of the chain. As further used herein, the term "pendent group" refers to any group that is covalently coupled to a polymeric strand in a position other than the backbone. An exemplary preferred adhesion promoter is shown in **Figure 2**.

Alternatively, suitable polymeric strands include all polymeric strands that have a plurality of unsaturated sites for sulfur crosslinking, or polymeric strands copolymerized of polybutadiene, polyisoprenes, styrene-butadiene copolymers (with a styrene content between about 0-35% by weight), styrene-butadiene-styrene terpolymers, or other appropriate dienes, all of which may further be maleinized. In further alternative aspects of the inventive subject matter, numerous polymeric strands other than a polybutadiene are also contemplated and such strands include organic, organo-metallic, and inorganic polymeric strands, and all reasonable combinations thereof. Organic polymers may be especially suitable, where it is desirable that the polymeric strand has substantially similar physicochemical properties (*e.g.*, flexibility, solubility, or reactivity). The term "substantially similar" as used herein means a difference of no more than 25%, preferably no more than 15%, and even more preferably no more than 10%. For example, where contemplated adhesion promoters are utilized as an adhesion promoter between an epoxy coated polymeric fiber (*i.e.*, a polymeric fiber having a plurality of epoxy groups, or coated with a compound having a plurality of epoxy groups) and a rubber composition, particularly contemplated alternative polymeric strands include copolymers and block copolymers of polybutadiene, polyisoprenes, etc. On the other hand, where rigidity is especially desirable, polyphenylenes, or other rigid-rod-type polymers may be included in or form the polymeric strand. Further contemplated organic polymers include polyesters, polyethers, polyimides, polyamides, and polycarbonates, all of which may or may not include aromatic or conjugated systems. Organo-metallic polymeric strands may be particularly advantageous where relatively high backbone strength is desirable, and especially contemplated alternative organo-

metallic polymeric strands include a siloxane backbone with alkyl or aryl side chains. Contemplated inorganic polymeric chains may be advantageous where relatively high temperature resistance is particularly desired, and suitable polymeric chains include silica and alumina based polymeric chains and three-dimensional networks of such chains.

5 It should further be appreciated that the length of suitable polymeric strands may vary considerably, and it is generally contemplated that appropriate polymeric strands may comprise between 15-2000 monomers, and more, but preferably between 15-200 monomers. The term "monomer" as used herein refers to any repeating molecular entity that forms at least a portion of a polymeric strand, wherein the repeating molecular entity may be identical (*e.g.*, in a homopolymer) or different (*e.g.*, in a heteropolymer). For example, a particularly suitable molecular weight in preferred polymeric strands (*e.g.*, polybutadiene) is between about 2000–5000. Consequently, with the molecular weight of butadiene monomer (54), preferred polymeric strands will have between about 37-92 monomers. However, the number of monomers may also be higher in alternative polymeric strands (*e.g.*, between 100 and 2000, and more). Consequently, the molecular weight of contemplated polymeric strands may range from about 200-5000Dalton (in some cases even less) to about 100,000 Dalton to approximately 1,000,000 Dalton, and more.

10
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10

dienophile groups disposed within the backbones. Alternatively, where a vulcanization step is included in processing a rubber composition, especially preferred crosslinking groups are double bonds, which may or may not be located within the backbone of a polymeric strand.

On the other hand, where it is desirable to couple two polymeric strands at a relatively large distance, additional crosslinkers may be employed to provide a spacer. Consequently, such additional crosslinkers will have at least two reactive groups, wherein each of the two groups will participate in a reaction coupling the crosslinker to the polymeric strands. Depending on the chemical nature of the crosslinker, contemplated crosslinking groups may vary considerably and will include nucleophilic groups, electrophilic groups, photo-reactive groups, polar groups, non-polar groups, etc. For example, where a crosslinker has a nucleophilic group (*e.g.*, an amine), contemplated crosslinking groups may include anhydrides, activated acids, activated esters, etc. Similarly, where the crosslinker has a plurality of electrophilic groups, the crosslinking groups in the polymeric strands may include alcohols, thiols, amines, etc. Consequently, contemplated crosslinking reactions include various types of reaction and will predominantly depend on the particular chemical nature of the crosslinking group. For example preferred crosslinking reactions include formation of a covalent bond with a sulfur atom, and further include nucleophilic and electrophilic additions, eliminations, or substitutions, cycloadditions, Michael additions, etc.

It should further be appreciated that the number of contemplated crosslinking groups in a polymeric strand may differ among various applications. For example, where a high degree of crosslinking is desired, substantially all of the monomers may include a crosslinking group. On the other hand, where a high degree of crosslinking is not particularly desirable, the number of crosslinking groups may be as significantly lower and will typically between 1 crosslinking group per 2-20 monomers, in some cases 1 crosslinking group per 20-200 monomers, and in less contemplated cases 1 crosslinking group per 200 monomers, and more. Furthermore, it should be appreciated that more than one type of crosslinking group may be employed in a polymeric strand to add a particular crosslinking specificity. For example, it is particularly contemplated that hydrogen-bond donor or acceptor groups may be included into the polymeric strands as a first type of crosslinking group, while the second type of crosslinking group may form a covalent bond (*e.g.*, in a vulcanizing reaction). Thus, it should be appreciated that crosslinking two polymeric strands may

employ covalent bonds, but also non-covalent bonds, including hydrogen bonds, ionic interaction, hydrophobic interaction, etc.

In further alternative aspects of the inventive subject matter, the epoxy-reactive group need not be limited to a carboxylic acid group from a maleic acid moiety and numerous alternative epoxy-reactive groups are also contemplated. It is generally contemplated that all chemical groups that can form a covalent bond with an epoxy group are suitable in conjunction with the teachings presented herein, however, particularly contemplated epoxy-reactive groups include nucleophilic groups such as non-phenolic (primary, secondary, and tertiary) hydroxyl groups, amine groups, or sulfohydri groups. It should further be appreciated that suitable epoxy-reactive groups may be positioned in the polymeric strand at various locations, including terminal positions, pendent positions, and within the backbone or other positions in the polymeric strand, and all reasonable combinations thereof. For example, where it is desirable to couple the polymeric strand at a relatively large distance from an epoxy group, suitable epoxy-reactive groups may be pendent groups on a terminal position of a C₄-C₂₀ arm. On the other hand, where it is desirable to couple the polymeric strand at a relatively short distance from an epoxy group, suitable epoxy-reactive groups may be pendent groups on a terminal position of a C₁-C₃ arm, or even be positioned within the backbone or terminus of the polymeric strand. With respect to the number of the epoxy-reactive groups, it should be recognized that the exact number is not limiting to the inventive subject matter, however, it is generally contemplated that suitable polymeric strands will have at least one, preferably between 2-10 epoxy-reactive groups per 1000Dalton. In some instances, contemplated polymeric strands may have between 10-15, or even more epoxy-reactive groups per 1000Dalton.

While it is generally contemplated that the epoxy-reactive groups are chemically identical within one polymeric strand, it is also contemplated that where desirable, more than one type of epoxy-reactive groups may be included. For example, a polymeric strand may have one type of epoxy-reactive group that directly reacts with an epoxy group, while another type of epoxy-reactive group may require an intermediary molecule (*e.g.*, a bifunctional crosslinker) to covalently couple the second epoxy-reactive group to the epoxy group.

It is still further contemplated that the epoxy-reactive groups, and especially where such groups are carboxylic acid groups, may also be involved in functions other than forming a covalent bond with an epoxy group, and contemplated functions particularly include formation of a hydrogen bond. However, it should be recognized that additional groups for alternative functions (*e.g.*, formation of non-covalent bonds) may be incorporated into the polymeric strand.

With respect to the epoxy group, it is contemplated that suitable epoxy groups may be located on numerous materials. For example, where contemplated polymeric strands are employed to couple rubber to a polymeric fiber (which may be fabricated into yarns or cords), the epoxy group may be an integral part (*i.e.*, covalently coupled) of the polymeric fiber, or may be disposed in a coating compound that is coated onto the fiber or yarn as an over-finish or spin-finish. There are numerous epoxy-containing coatings for fibers and yarns known in the art, and all of them are contemplated suitable for use herein. Typical epoxy-containing compounds used in spin finish or overfinish include (3-glycidoxypropyl)trimethoxysilane, glyceryl epoxide, sorbitol epoxide, novolak epoxy resins, epoxidized oils, epoxidized polybutadiene, or epoxidized polyisoprenes, wherein epoxies include compounds comprising glycidyl ether groups, and non- glycidyl ether groups such as cyclo aliphatic epoxies or acyclic epoxies. In still further alternative aspects, the epoxy group may be replaced with a chemically reactive group other than an epoxy group (*e.g.*, a nucleophilic or electrophilic group). Consequently, it should be appreciated that suitable epoxy-reactive groups may be groups other than previously contemplated groups and particularly include chemically reactive groups that will form a covalent bond with the chemically reactive group other than an epoxy group:

It should be particularly appreciated that contemplated adhesion promoters are water soluble in an amount of no less than 10g/l, preferably no less than 30g/l – 200g/l, and most preferably no less than 75g/l – 150g/l, and that water solubility may be achieved in numerous ways. For example, where the polymeric strand is relatively hydrophobic, hydrophilic groups may be added to the molecule at various positions. As depicted in Figure 2, a pendent methoxy polyethylene glycol (PEG) is added to the polymeric strand to afford a particular water solubility. Of course, it should be appreciated that the chain length and modification of suitable methoxy PEGs need not be restricted to a particular number of monomers (here: between 1-100) and particular type of end cap, but

numerous modifications can be made by a person of ordinary skill in the art. For example, alternative water solubilizing molecules (e.g., mono-hydroxyl or mono-amine terminated polyoxyalkylenes) may be added or may replace the methoxy-PEG. The term "water soluble" as used herein means that a compound can substantially completely (*i.e.*, at least 95wt%) be dissolved in water at 25°C. The term "dissolved" as used herein means that the compound passes into solution without remaining in, or forming a particulate form (e.g., precipitate or powder).

Particularly preferred modifying groups (e.g., polyalkylene oxides) will include a single reactive group (e.g., a single hydroxyl group) that reacts with a maleic anhydride located on the polymeric strand to form an ester group and a carboxylic acid group from the maleic anhydride. Moreover, it is particularly preferred that the modifying group will also include at least one chemical group that contributes to increased chemical compatibility and/or affinity between the adhesion promoter and a polymeric strand. For example, it is contemplated that increasing numbers of polyethylene oxide repeating units in a modifying group will increase water dispersibility and water solubility. Additionally, polyethylene oxide is known to exhibit significant affinity towards polyesters. Alternatively, modifying groups that may be employed include polyethylene oxide, polypropylene oxide or copolymers of propylene oxide and ethylene oxide, polyamide, polyacrylamide, etc.

It should be particularly appreciated that water solubility of contemplated adhesion promoters greatly reduces, if eliminates, the need of an organic solvent other than H₂O, thereby advantageously reducing environmental impact, potential health hazards to operators, and cost of proper disposal of such solvents. Still further, contemplated adhesion promoters may at least partially, and more typically completely eliminate the use of RFL (resorcinol-formaldehyde-latex), a composition well known to be problematic in numerous respects. For example, formaldehyde is a toxic and cancer suspect agent. Furthermore, RFL typically requires an ageing period (reaction of resorcinol with formaldehyde) prior to use in rubber containing products, whereas there is no particular pretreatment (*e.g.*, activation) required with contemplated adhesion promoters. In yet further alternative aspects of the inventive subject matter, it is contemplated that addition of PEG not only affords increased water solubility, but also provides a plurality of hydrogen bond donor/acceptor groups. Thus, it is contemplated that suitable adhesion promoters include a moiety

that provides at least 2, more preferably at least 4, and most preferably at least 7 hydrogen donor and/or acceptor groups. Such hydrogen donor and/or acceptor groups may be located in any portion of the adhesion promoter (including the backbone and a pendent group), however, it is particularly preferred that the hydrogen donor and/or acceptor group is covalently coupled to a carboxylic acid group, which is coupled to the polymeric strand. While not wishing to be bound to a particular theory, it is contemplated that hydrogen donor and/or acceptor groups additionally or synergistically increase bonding strength between an epoxy-containing polymeric fiber and a rubber composition comprising a maleinized polybutadiene.

Moreover, it is further contemplated that addition of polyethylene glycol may increase the chemical compatibility of the adhesion promoter with the surface of the fiber. Consequently, it is contemplated that suitable adhesion promoters may include a polar group or a hydrogen bond donor- or acceptor group, where the fiber has a plurality of polar groups and/or hydrogen bond donor- or acceptor groups. Likewise, suitable adhesion promoters may include additional hydrophobic groups where the fiber has a plurality of hydrophobic and/or non-polar groups.

In a particularly preferred aspect of the inventive subject matter, contemplated adhesion promoters are employed to couple an epoxy group-comprising fiber or yarn to a rubber or rubber composition. While it is generally contemplated that suitable adhesion promoters may be employed by themselves, it should be appreciated that a second polymer may be added to contemplated adhesion promoters. For example, an especially contemplated second polymer comprises a styrene-butadiene-vinylpyridine copolymer as depicted in **Figure 3**. Addition of second polymers are contemplated to increase (additionally or synergistically) the adhesion between the rubber and the polymeric fiber or yarn (*infra*). While not wishing to be bound by a particular theory, it is contemplated that additional polymers crosslink with the rubber, while forming hydrogen (or other covalent or non-covalent) bonds with contemplated adhesion promoters.

Contemplated rubbers include various natural and synthetic rubbers, and all reasonable combinations thereof, and may further include maleinized polybutadiene, maleinized polyisoprenes, maleinized styrene-butadiene-copolymers, or epoxidized polyisoprene. It is especially contemplated that addition of maleinized polybutadiene to contemplated rubbers in combination with contempla-

ted adhesion promoters further increases adhesion between the polymeric fiber or yarn and the rubber (*infra*).

Consequently, it is contemplated that a rubber containing product comprises a polymeric fiber coated with a compound having a plurality of epoxy groups, wherein the polymeric fiber is coupled to a rubber via an adhesion promoter, wherein the adhesion promoter comprises a polymeric strand with an epoxy-reactive group other than a phenolic hydroxyl group, and further comprises a crosslinking group that crosslinks the polymeric strand with the rubber, and wherein the adhesion promoter is water soluble in an amount of no less than 10g/l, preferably no less than 100g/l. An exemplary rubber containing product is depicted in **Figure 5A**. The product 500A (*e.g.*, a tire, power transmission belt, conveyor belt, etc.) comprises a polymeric fiber 510A with a plurality of epoxy groups 512A coated onto the polymeric fiber. The adhesion promoter 520A has a plurality of crosslinking groups 522A and a plurality of epoxy-reactive groups 524A other than a phenolic hydroxyl group. The epoxy-reactive groups 524A form a covalent bond with the epoxy groups 512A, and the adhesion promoter 520A is covalently coupled to a rubber 530A via a covalent bond 523A (*e.g.*, via sulfur crosslinking).

There are numerous polymeric fibers known in the art, and all of the known polymeric fibers and yarns produced from such polymeric fibers are contemplated suitable for use in conjunction with the teachings presented herein. Particularly preferred polymeric fibers include polyester fibers (*e.g.*, polyethylene terephthalate and polyethylene naphthalate) and polyamide fibers. With respect to structure and solubility of the adhesion promoter, the compound having a plurality of epoxy groups, and the rubber, the same considerations apply as described above.

It is still further contemplated that appropriate rubber containing products may further comprise a styrene-butadiene-vinylpyridine copolymer (as part of the adhesion promoter), wherein at least a portion of the styrene-butadiene-vinylpyridine copolymer is coupled to the rubber via sulfur crosslinking, and wherein another portion of the styrene-butadiene-vinylpyridine copolymer is coupled to the acid-modified maleinized polybutadiene (via complexation of nitrogen in pyridine by acid groups in acid modified polybutadiene) as shown in **Figure 5B**. The product 500B (*e.g.*, a tire, power transmission belt, conveyor belt, etc.) comprises a polymeric fiber 510B with a plurality of

epoxy groups 512B coated onto the polymeric fiber. The acid-modified maleinized polybutadiene 520B has a plurality of crosslinking groups 522B and a plurality of epoxy-reactive groups 524B other than a phenolic hydroxyl group. The epoxy-reactive groups 524B form a covalent bond with the epoxy groups 512B, and the acid-modified maleinized polybutadiene 520B is covalently coupled to a rubber 530B via a covalent bond 523B (via sulfur crosslinking). The styrene-butadiene-vinylpyridine terpolymer 540B is covalently coupled to the rubber 530B via covalent bonds 542B, and to the acid modified polybutadiene 520B via complexation bond 541B.

Figure 6A depicts another exemplary schematic of a rubber containing product according to the inventive subject matter, in which the product generally comprises 4 components. (1) A rubber component that may comprise natural rubber, and optionally any synthetic rubbers, accelerators, activators, sulfur and other standard rubber additives. The rubber further comprises maleinized polybutadiene (or any other polyunsaturated maleinized polymer). (2) A Coating comprising an adhesion promoter (here: an acid modified polybutadiene) and a second polymer (here: a styrene-butadiene-vinyl pyridine latex). (3) A fiber (here: a polyester fiber), and (4) A plurality of epoxy groups on the fiber surface. **Figure 6B** depicts the chemical composition of some of the components of the rubber containing product as shown in Figure 6A. **Figure 7** shows some of the contemplated interactions between the maleinized polybutadiene in the rubber, the exemplary adhesion promoter and the second polymer in the adhesive coating, and the epoxy groups on the surface of a polymeric fiber.

Thus, a method of fabricating a rubber containing product comprises a step in which a rubber, and a polymeric fiber comprising a plurality of epoxy groups are provided. In a further step, an adhesion promoter is provided having a polymeric strand with an epoxy-reactive group other than a phenolic hydroxyl group, and further having a crosslinking group, and wherein the adhesion promoter is water soluble in an amount of no less than 10g/l, preferably no less than 100g/l. In yet another step, the rubber is covalently coupled with the polymeric fiber via the adhesion promoter, wherein the epoxy-reactive group forms a covalent bond with the epoxy group, and wherein the crosslinking group forms another covalent bond with the rubber.

In particularly preferred alternative aspects of contemplated methods, the methods may further comprise a step in which a styrene-butadiene-vinylpyridine copolymer is provided and at least a portion of the styrene-butadiene-vinylpyridine copolymer is coupled to the rubber. Additionally, it is contemplated that a maleinized polybutadiene may further be admixed with the rubber.

5 Examples

The following examples provide exemplary synthesis and use of contemplated adhesion promoters. Particularly contemplated examples include rubber-containing products with increased adhesion of a polymeric fiber to a rubber composition.

Preparation of an Acid Modified Polybutadiene resin

An exemplary synthetic scheme of an acid modified polybutadiene is depicted in **Figure 4**, and an exemplary synthetic protocol is as follows: 222 grams (0.0435 moles) of a maleinized polybutadiene (Mn = 5,100; anhydride equivalent weight = 577, available from Ricon Resins as Ricon 131MA17) were weighed in a 500-ml, 3-neck round bottom flask equipped with a mechanical stirrer, nitrogen purge inlet and a condenser. Subsequently, 172 grams (0.4914 moles) of polyethylene glycol monomethyl ether (Mn = 350; available from Union Carbide as Carbowax Methoxypolyethylene glycol 350) were added with 0.0774 grams of pentaerythritol, tetrakis(3,5-di-tert-butyl-4-hydroxyhydrocinnamate) (available as Irganox 1010 from Ciba Specialty Chemicals). The reaction vessel was closed and nitrogen was continuously purged through the system. The reaction was heated under vigorous stirring at 160°C for 9 hours. The progress of the reaction was monitored by IR spectroscopy. The IR spectra showed the complete disappearance of the anhydride peaks at 1863 cm⁻¹ and 1784 cm⁻¹ and the appearance of ester carbonyl peak at 1737 cm⁻¹. The reaction product is a brown, transparent, viscous liquid (with an acid content of 1.1 milliequivalents of acid per gram of resin) (hereinafter referred to as *Polymer A*).

Where maleic anhydride is employed in the synthesis of contemplated adhesion promoter, it is generally contemplated that the content of maleic anhydride in the polyunsaturated polymer may vary from 1-30wt%, preferably between 10-35%, and more preferably between 15 and 20%. For coating applications, it is particularly contemplated that the maleic anhydride content should be selected such that the resulting acid modified polymer (*i.e.*, after reaction with the modifying group;

here: methoxy polyethylene glycol) has a sufficient amount of modifying groups to solubilize the polymeric strand in water.

Preparation of Coatings and Treated Polyester Cords

PET cords were prepared by twisting 1000 denier PET yarns into a 2-ply construction with 9.5x9.5 twists per inch. The original yarns either have a standard spin finish or an adhesive activated overfinish (greige cords).

The greige cords were subsequently treated with either (a) a conventional RFL (resorcinol-formaldehyde-latex) adhesive coating (for comparative purpose) or (b) the coatings as described herein using a single-end Litzler Computreator. Treating conditions were as follows: first, the cord was passed through a dip tank containing the coating. Dip pick up was controlled between 5-6 weight percent. The emerging dipped cord then passed through a first hot air oven at 350°F for 60 seconds followed by a second hot air oven at 475°F for 60 seconds. The composition of the coatings that were used for treating the PET cords are as follows:

Control RFL	Resorcinol-Formaldehyde-Latex
Coating 1	Prepared by dispersing 80 grams of Polymer A (as prepared in Example above) with 800 grams of deionized water
Coating 2	Vinylpyridine-Butadiene-Styrene latex (15 percent vinyl pyridine / 70 percent butadiene / 15 percent styrene) available as GenTac 118 from Omnova Solutions Inc. diluted to 20 weight percent solids with deionized water
Coating 3	Mixture containing equal parts by weight of Coating 1 and Coating 2
Coating 4	Prepared by dissolving 0.8 grams of 2-ethyl-4-methyl-imidazole and 80 grams of Polymer A (prepared as described in Example 1) in 800 grams of deionized water
Coating 5	Mixture of equal parts of Coating 2 and Coating 4
Coating 6	Ricon FX 9966 (maleinized polybutadiene latex available from Ricon Resins)

Preparation of Rubber Coupons for Adhesion Testing

ASTM method D2229-98 was adopted for the adhesion testing of the polyester tire cords to rubber. The standard rubber formulation used to prepare the test coupons for the Peel Adhesion Test is as follows (expressed as parts by weight): 37 parts of natural rubber, 8.4 parts of styrene-butadiene rubber, 14.4 parts of polybutadiene rubber, 28 parts carbon black, 3.8 parts activators / accelerators, 1.3 parts sulfur and 7.1 parts of plasticizers, tackifiers and antioxidants. For the modified rubbers, the appropriate maleinized polybutadiene resin was compounded with the standard rubber at 3, 5 and 10 weight percent depending on the desirable test rubber.

The treated cord was then wound on a winding drum (6.5 inches in diameter, that was wrapped with a strip of test rubber) to form a pad of 6 inches in width with an average of about 36-40 ends per inch. The cord/rubber pad was removed from the drum, laid flat on a work bench with the exposed cord side facing up. A strip of backing rubber was then placed on the top of the cord surface to form the complete test pad. Two 6 inches by 8 inches sections were cut from the test pad and strips of separator cloth (1 inch in width) were placed at each end of the sections. One section was placed on the top of the other with the test rubber layers facing each other. The combined test pad was subsequently cured at 350°F for 6 minutes under 333 psi pressure. The cured test pad was conditioned for a minimum of 16 hours at 75°F prior to testing. Test strip samples (1 inch by 4 inches) were cut from the cured pad.

Peel Adhesion Test

The hot peel test was carried out using an Instron Tensile tester at a pull rate of 4 inches per minute. The test strips were conditioned in an oven at 250°F for 30 minutes and pulled apart immediately after removing from the oven. The maximum force required to pull the test coupon apart is reported as the peel strength in lbs/in (pounds per inch). Visual rating (grade) was determined according to the percentage of rubber still observable on the cord surface after the two parts of the strip have been pulled apart. A "0 rating" corresponds to no rubber coverage or adhesive

failure at the rubber/cord interface and a " 5 rating" means that there is 100% rubber coverage indicating a cohesive failure of the rubber and good adhesion between the cord and the rubber.

5

Adhesion using Acid Modified Polybutadiene and Synergistic Effect of Acid Modified Polybutadiene and Vinyl Pyridine-Butadiene-Styrene Latex

Table 1 shows the Peel Adhesion Test data of PET cords with two different adhesive activated overfinishes, and treated with different coatings (preparation see above) according to the inventive subject matter. For comparative purpose, the PET cord was also treated with a standard RFL (resorcinol-formaldehyde-latex) adhesive composition that is being widely used in the tire industry to treat the tire cords.

204710-523501

Table 1

	<u>Peel Strength</u> (lbs/in) ⁽¹⁾	<u>Visual Rating</u>
Overfinish 1		
Greige cord	8.5	0
Coating 1	8.3	1
Coating 2	8.2	0.7
Coating 3	21.2	4.3
Overfinish 2		
Greige cord	8.3	0
Coating 1	7.2	0
Coating 2	6.1	0
Coating 3	23.3	4.1
Control RFL	37.2	4.9
(1) Adhesion data tested with standard rubber		

As can be seen from Table 1, cords treated with either an acid modified polybutadiene (Coating 1) or a vinyl pyridine-butadiene-styrene latex (Coating 2)(VP/B/ST latex) exhibited adhesion to at least some degree. Remarkably, when the acid modified polybutadiene is combined with the VP/B/S latex (Coating 3), significant improvement in peel adhesion strength is observed.

10 The inventors contemplate, that the synergistic effect on adhesion is likely due to interaction between the acid groups of the acid modified polybutadiene and the vinyl pyridine of the VP/B/ST latex.

Comparison of Adhesion Performance of Acid Modified Polybutadiene Latex and Maleinized Polybutadiene Latex ⁽⁴⁾

Coating 1 = Acid modified Polybutadiene of this invention. Coating 2 = Vinyl pyridine-
5 Butadiene-Styrene Latex. Coating 6 = Maleinized Polybutadiene Latex.

Table 2

	Standard rubber		PBMA Rubber ⁽¹⁾		HRH Rubber ⁽²⁾	
	Peel Strength (lbs/in)	Visual Rating	Peel Strength (lbs/in)	Visual Rating	Peel Strength (lbs/in)	Visual Rating
(1) Greige cord	2.9	1			35.3	4.8
(2) Coating 6	10.7	1.8	10.4	0	12	1.2
(3) Coating 6 and Coating 2 ⁽³⁾	15	2	3.5	0	17.7	1.7
(4) Coating 1	6.4	0.8	18.5	1.2	23.1	2.2
(5) Coating 1 and Coating 2 ⁽³⁾	22.8	3.3	48	4.4	41.5	4.4
(6) Control RFL	38	5				

- (1) Standard rubber modified with 10 wt% of maleinized polybutadiene (PBMA; Mn = 5100; 17 weight percent maleic anhydride; available as Ricon 1731 from Ricon Resins Inc.)
 (2) Standard rubber modified with HRH (hexamethylene tetramine / resorcinol / silica) adhesion promoter system
 (3) Double dip system : first coating was applied before first oven, second coating was applied after passing through first oven, before going through second oven
 (4) "Maleinized Polybutadiene Latex for Fiber to Rubber Adhesion", by A. S. Estrin and R. W. Nalepa, Paper presented at the 155th Rubber Division , American Chemical Society, Chicago, Illinois April 13-16, 1999

The data in Table 2 clearly illustrate the surprising increase in effectiveness of contemplated
 10 adhesion promoters (here: acid modified polybutadiene as prepared in example above) in promoting adhesion as compared to maleinized polybutadiene latex as previously described. Furthermore, it can be seen that contemplated adhesion enhancers are significantly more effective than the maleinized polybutadiene latex in improving adhesion of polyester cords to various rubbers with a pronounced improvement when modified rubbers were used.

Effect of Modified Rubber on Adhesion

To investigate if the rubber composition may have a further influence on the adhesion, modified rubber compositions including maleinized polybutadiene were prepared. Surprisingly, as indicated in Table 3, addition of maleinized polybutadiene into the rubber further increased the adhesion of the rubber to the polymeric fibers when adhesion promoters according to the inventive subject matter were employed.

Table 3

PET Cords having different overfinishes and coated with Coating 5	<u>Standard rubber</u>		<u>Modified Rubber</u> <u>3% PBMA⁽¹⁾</u>		<u>Modified Rubber</u> <u>5% PBMA⁽¹⁾</u>	
	Peel Strength (lbs/in)	Visual Rating	Peel Strength (lbs/in)	Visual Rating	Peel Strength (lbs/in)	Visual Rating
Overfinish 1	16.5	4	22.1	3.8	20.6	3.3
Overfinish 2	15.3	3	22.7	4.2	25.1	4.2
Overfinish 3	21.2	4.3	23.4	4.2	34.8	4.2
Overfinish 4	21.8	2.8	-	-	29.6	4.1
Control RFL	34.3	4.8	-	-	-	-

(1) Standard rubber modified with maleinized polybutadiene (PBMA; Mn = 5100; 17 weight percent maleic anhydride; available as Ricon 1731 from Ricon Resins Inc.)

It can be seen from Table 3 that the combined use of (a) a coating from a blend of an acid modified polybutadiene with vinyl pyridine-butadiene-styrene latex and (b) a rubber modified with maleinized polybutadiene showed peel strength adhesion equivalent to the control RFL system.

Consequently, it should be especially recognized that adhesion of polymeric fibers to rubber may be significantly improved by including adhesion promoters according to the inventive subject matter, and especially an acid modified polybutadiene in combination with a second polymer (especially vinyl pyridine-butadiene-styrene latex). While not wishing to be bound by a particular theory, the inventors contemplate that there is a synergistic effect between the acid modified polybutadiene and the vinyl pyridine-butadiene-styrene latex, which may be attributed to the acid-base interactions between the two polymer systems.

Furthermore, it should be appreciated that polyethylene oxide acid modified polybutadiene as described herein are surprisingly and significantly more effective than the ammonium hydroxide / sodium hydroxide or potassium hydroxide maleinized polybutadiene latex as described previously. Still further, the combined use of an acid modified polybutadiene / vinyl pyridine-butadiene-styrene latex coating with a maleinized polybutadiene rubber showed improved adhesion of polyester cords equivalent to the current RFL system. Therefore, adhesion promoters according to the inventive subject matter may provide a formaldehyde-free coating, which may be an environmentally sensible replacement for the current RFL systems.

Thus, specific embodiments and applications of adhesion promoters with epoxy-reactive groups have been disclosed. It should be apparent, however, to those skilled in the art that many more modifications besides those already described are possible without departing from the inventive concepts herein. The inventive subject matter, therefore, is not to be restricted except in the spirit of the appended claims. Moreover, in interpreting both the specification and the claims, all terms should be interpreted in the broadest possible manner consistent with the context. In particular, the terms "comprises" and "comprising" should be interpreted as referring to elements, components, or steps in a non-exclusive manner, indicating that the referenced elements, components, or steps may be present, or utilized, or combined with other elements, components, or steps that are not expressly referenced.

1053275.11700